

# 1.75CR Sirocco Mini Shock Fall Arrest Lanyard



Lightweight 1.75m fall arrest lanyard featuring a heat- and cut-resistant Technora® braid rope, designed for enhanced safety in extreme environments.

The MiniShock Cut Resistant Fall Arrest Lanyard (1.75CR) is engineered to provide reliable fall protection for personnel operating in challenging conditions. Its Technora® braid rope offers exceptional resistance to heat (up to 500°C) and abrasion, ensuring durability in high-risk environments. The integrated MiniShock energy absorber is rated for users up to 140kg and accommodates Fall Factor 2 scenarios, effectively reducing impact forces during a fall. Additionally, the lanyard includes a protective sleeve with an integrated ring for pole chocking, enhancing versatility in various applications. The device is equipped with a double-action black snap hook and a triple-lock karabiner for secure connections. Compliant with EN 355:2002, EN 362:2004/T, and EN 1891A standards, the 1.75CR is ideal for use in the utility and industrial sectors.

#### Key Features:

- 1.75m lanyard with Technora® braid rope for heat and cut resistance
- Integrated MiniShock energy absorber rated to 140kg, suitable for Fall Factor 2
- Protective sleeve with integrated ring for pole chocking
- Double-action black snap hook and triple-lock karabiner for secure attachment

<b>Product Code:</b>	<b>1.75CR</b>
<b>Conformance:</b>	<b>EN 355, EN 362, EN 1891A</b>
<b>Max User Weight:</b>	<b>140kg</b>
<b>Length:</b>	<b>1.75m</b>
<b>Materials:</b>	<b>Aluminium components; Technora® 32-braid rope with nylon core; Alloy karabiner</b>